

Bullnose endmill 2F

เอ็นมิลคาร์ไบด์ บูลโนส 2 ฟัน



Application :
Steel < 56HRC, Cast iron, Stainless, Copper

B265X

Dc h10	R	Lc mm	L mm	Shank h6
3.0	R0.3	8	50	6
3.0	R0.5	8	50	6
4.0	R0.3	11	50	6
4.0	R0.5	11	50	6
5.0	R0.3	13	50	6
5.0	R0.5	13	50	6
6.0	R0.3	16	50	6
6.0	R0.5	16	50	6
6.0	R1.0	16	50	6
6.0	R1.5	16	50	6
8.0	R0.3	20	60	8
8.0	R0.5	20	60	8
8.0	R1.0	20	60	8
8.0	R1.5	20	60	8
8.0	R2.0	20	60	8
10.0	R0.5	22	72	10
10.0	R1.0	22	72	10
10.0	R1.5	22	72	10
10.0	R2.0	22	72	10
10.0	R3.0	22	72	10
12.0	R0.5	26	75	12
12.0	R1.0	26	75	12
12.0	R1.5	26	75	12
12.0	R2.0	26	75	12
12.0	R3.0	26	75	12



** Bullnose รุ่นยาว B267X / B268X กรุณาสอบถาม

Bullnose endmill 4F

เอ็นมิลคาร์ไบด์ บูลโนส 4 ฟัน



Application :
Steel < 56HRC, Cast iron, Stainless, Copper

B266X

Dc h10	R	Lc mm	L mm	Shank h6
3.0	R0.3	8	50	6
3.0	R0.5	8	50	6
4.0	R0.3	11	50	6
4.0	R0.5	11	50	6
5.0	R0.3	13	50	6
5.0	R0.5	13	50	6
6.0	R0.3	16	50	6
6.0	R0.5	16	50	6
6.0	R1.0	16	50	6
6.0	R1.5	16	50	6
8.0	R0.3	20	60	8
8.0	R0.5	20	60	8
8.0	R1.0	20	60	8
8.0	R1.5	20	60	8
8.0	R2.0	20	60	8
10.0	R0.5	22	72	10
10.0	R1.0	22	72	10
10.0	R1.5	22	72	10
10.0	R2.0	22	72	10
10.0	R3.0	22	72	10
12.0	R0.5	26	75	12
12.0	R1.0	26	75	12
12.0	R1.5	26	75	12
12.0	R2.0	26	75	12
12.0	R3.0	26	75	12



Long-neck ballnose

เอ็นมิลคอยาว หัวบอล



Application :
Steel < 68HRC ,Copper

F695GX

R	L1 mm	Lc mm	L mm	Shank h6
±0.01				
0.15R	2	0.24	50	4
0.15R	3	0.24	50	4
0.2R	2	0.30	50	4
0.2R	4	0.30	50	4
0.25R	4	0.4	50	4
0.25R	6	0.4	50	4
0.25R	8	0.4	50	4
0.3R	4	0.5	50	4
0.3R	6	0.5	50	4
0.3R	8	0.5	50	4
0.4R	4	0.6	50	4
0.4R	6	0.6	50	4
0.4R	8	0.6	50	4
0.4R	10	0.6	50	4
0.5R	4	0.8	50	4
0.5R	6	0.8	50	4
0.5R	8	0.8	50	4
0.5R	10	0.8	50	4
0.5R	12	0.8	50	4
0.5R	16	0.8	50	4
0.5R	20	0.8	50	4
0.75R	6	1.2	50	4
0.75R	8	1.2	50	4
0.75R	10	1.2	50	4
0.75R	12	1.2	50	4
0.75R	16	1.2	50	4
0.75R	20	1.2	50	4
1.0R	6	1.6	50	4
1.0R	8	1.6	50	4
1.0R	10	1.6	50	4
1.0R	12	1.6	50	4
1.0R	16	1.6	50	4
1.0R	20	1.6	60	4
1.0R	25	1.6	60	4
1.0R	30	1.6	70	4
1.5R	6	2.4	50	6
1.5R	8	2.4	50	6
1.5R	10	2.4	50	6
1.5R	12	2.4	50	6
1.5R	16	2.4	60	6
1.5R	20	2.4	60	6
1.5R	25	2.4	70	6
1.5R	30	2.4	70	6
1.5R	35	2.4	80	6
2.0R	8	3.2	60	6
2.0R	10	3.2	60	6
2.0R	12	3.2	60	6
2.0R	16	3.2	60	6
2.0R	20	3.2	70	6
2.0R	25	3.2	70	6
2.0R	30	3.2	80	6
2.0R	35	3.2	80	6
2.0R	40	3.2	90	6
2.0R	45	3.2	100	6
2.0R	50	3.2	100	6



**ขนาดอื่น ๆ นอกจากนี้ กรุณาสอบถามเพิ่มเติม

Long-neck flat endmill

เอ็นมิลคอยาว 2 ฟัน - 4 ฟัน



Application :
Steel < 68HRC ,Copper

F692GX 2 ฟัน
F694GX 4 ฟัน

Dc	L1 mm	Lc mm	L mm	Shank h6
±0.02				
0.3	2	0.45	50	4
0.3	4	0.45	50	4
0.4	2	0.6	50	4
0.4	4	0.6	50	4
0.5	2	0.7	50	4
0.5	4	0.7	50	4
0.5	6	0.7	50	4
0.5	8	0.7	50	4
0.5	10	0.7	50	4
0.6	4	0.9	50	4
0.6	6	0.9	50	4
0.6	8	0.9	50	4
0.6	10	0.9	50	4
0.8	4	1.2	50	4
0.8	6	1.2	50	4
0.8	8	1.2	50	4
0.8	10	1.2	50	4
1.0	4	1.5	50	4
1.0	6	1.5	50	4
1.0	8	1.5	50	4
1.0	10	1.5	50	4
1.0	12	1.5	50	4
1.0	16	1.5	50	4
1.0	20	1.5	50	4
1.5	6	2.3	50	4
1.5	8	2.3	50	4
1.5	10	2.3	50	4
1.5	12	2.3	50	4
1.5	16	2.3	50	4
1.5	20	2.3	50	4
2.0	6	3.0	50	4
2.0	8	3.0	50	4
2.0	10	3.0	50	4
2.0	12	3.0	50	4
2.0	16	3.0	50	4
2.0	20	3.0	60	4
2.0	25	3.0	60	4
2.0	30	3.0	70	4
3.0	8	4.5	50	6
3.0	10	4.5	50	6
3.0	12	4.5	50	6
3.0	16	4.5	60	6
3.0	20	4.5	60	6
3.0	25	4.5	70	6
3.0	30	4.5	70	6
3.0	35	4.5	80	6
4.0	12	6.0	60	6
4.0	16	6.0	60	6
4.0	20	6.0	70	6
4.0	25	6.0	70	6
4.0	30	6.0	80	6
4.0	35	6.0	80	6
4.0	40	6.0	90	6
4.0	45	6.0	100	6
4.0	50	6.0	100	6



*เอ็นมิลคอยาว 4 ฟัน Code: F694GX เริ่มที่ 1.0mm

**เอ็นมิลคอยาว Bullnose (รุ่นมี R) Code: F690GX

● สต็อกสินค้าพร้อมส่งทุกรุ่น

A

Milling

B

Turning

C

Drilling

D

Tapping

E

Boring Reamer

F

Polishing

G

Tooling system & Accessories

7