


### - Micro Diameter - 2F

微小徑鑽頭-標準型(3mm柄)

## DGM-NA2



Order No. 訂購編號	Dia. 刃徑 (d)	CL 刃長 (L1)	OAL 全長 (L)	Shank 柄徑 (D)
DGMNA200305	0.30	5.0	38	3
DGMNA200355	0.35	5.0	38	3
DGMNA200405	0.40	7.0	38	3
DGMNA200455	0.45	7.0	38	3
DGMNA200505	0.50	7.0	38	3
DGMNA200605	0.60	8.0	38	3
DGMNA200705	0.70	8.0	38	3
DGMNA200805	0.80	8.0	38	3
DGMNA200905	0.90	8.0	38	3
DGMNA201005	1.00	8.0	38	3
DGMNA201105	1.10	8.0	38	3
DGMNA201205	1.20	8.0	38	3
DGMNA201305	1.30	8.0	38	3
DGMNA201405	1.40	8.0	38	3
DGMNA201505	1.50	8.0	38	3
DGMNA201605	1.60	8.0	38	3
DGMNA201705	1.70	8.0	38	3
DGMNA201805	1.80	8.0	38	3
DGMNA201905	1.90	8.0	38	3
DGMNA202005	2.00	8.0	38	3
DGMNA202105	2.10	8.0	38	3
DGMNA202205	2.20	8.0	38	3
DGMNA202305	2.30	8.0	38	3
DGMNA202405	2.40	8.0	38	3
DGMNA202505	2.50	8.0	38	3
DGMNA202605	2.60	8.0	38	3
DGMNA202705	2.70	8.0	38	3
DGMNA202805	2.80	8.0	38	3
DGMNA202905	2.90	8.0	38	3
DGMNA203005	3.00	8.0	38	3

### Dimension

- Win 038A
- 25~35 Degree Helix Angle
- 130 Degree Tip Angle
- Uncoating
- S-Fire Coating

### Tolerance

- d h7
- D h6

### Material

- Non-Ferrous
- ALUMINUM
- COPPER

### Recommend Cutting Condition